

High Power

Multi-Color LED Lamp

- SPECIFICATION -



LED116-12-



LED127-F



LED110 - 00


ELECTRONIC SPECIFICATONS

| Parameter | LED116-12-I-F | MCL127-00 | LED110 - I - 00 | | |
|--------------------------|--|-------------|-----------------|--|--|
| Power Spec. | | | | | |
| Power Voltage | 9 ~ 18 Vac 9 ~ 24 Vdc | 100~240 Vac | 100~240 Vac | | |
| Power Supply Current | < 600 mA | < 50 mA | < 50 mA | | |
| Power Consumption | 5W | 5W | 5W | | |
| Function Spec. | | | | | |
| Color Change Mode | 1 sec. change color / 5 sec change color / Fade change / Smooth change | | | | |
| Default Mix Color | 16 colors | | | | |
| Optical Spec. | | | | | |
| Operating Life | 20000 hr | | | | |
| Luminous Flux(typ.) | 185 lm | | | | |
| Environment Spec. | | | | | |
| Operation Temperature | -20~50 | | | | |
| Storage Temperature | -40~60 | | | | |
| Operation Humidity | 10~90 | | | | |


DIMENSION DAIGRAM

Unit: mm

LED116-12-I-F



LED110 - I - 00



LED127-I-F

